DART SERVICE INSTRUCTION TO AMEND INSTALLATION INSTRUCTIONS IIN-D505-1057 REV. B,

INSTALLATION INSTRUCTIONS II505-1 REV. E. INSTRUCTIONS FOR CONTINUED AIRWORTHINESS ICA-D505-1057 REV. 1, AND INSTRUCTIONS FOR CONTINUED AIRWORTHINESS ICA505-1 REV. 3 OR LATER APPROVED REVISIONS

REF. TCCA STC: SH18-9, SH19-31 REF. FAA STC: SR04133NY, SR04387NY REF. EASA STC: 10067422, 10070898 REF. DGAC MEXICO STC: IA-623/2019, IA-645/2019

1.0 **PURPOSE**

The DART D505-1057-013/-014/-113/-114 Skidtube Installations (ref. TCCA STC SH19-31) do not allow Loop Clamps and L-Brackets of the DART 651.600X-series Emergency Float System (ref. TCCA STC SH18-9) to install per the float system's installation instructions. The purpose of this DART Service Instruction (DSI) is to provide instructions for alternative attachment locations for the float system's Loop Clamps and L-Brackets. The DSI 9865-011 kit is available that provides additional hardware for this change.

This DSI also corrects the torque value for T-Bolt Loop Clamps of the DART 651.600X-series Emergency Float System.

2.0 CHANGE: RELOCATION OF LOOP CLAMP AND L-BRACKETS

DATE

When installing the 651.600X-series Emergency Float System on a DART D505-1057-013/-014/-113/-114 Skidtube Installation, Figure 1 of this DSI may be used for alternate Loop Clamp and L-Bracket locations as follows:

- i) 601.4106 Loop Clamps (F/N 25) may be located as shown in Figure 1 and Sections A-A & B-B
- 601.0733 L-Brackets (F/N 51) may be located on the saddles at one of the saddle-to-skidtube bolt ii) locations as shown in Figure 1 and Section C-C.



REV. B

SCALE

NTS

The section views give suggested bolt lengths for each location. Longer or shorter bolts and additional washers may be used to ensure 1.5-2 threads in safety. Torque the AN3 bolts 20-25in.lbs (2.3-2.8 N.m). If required, touch-up paint finish with chemical film material (Alodine 1200 or 1201) per MIL-C-5541, one coat of MIL-P-85582 or MIL-P-23377 primer, and 2-3 coats of MIL-C-83285 polyurethane paint to match original finish.




FIGURE 1: LOOP CLAMP AND L-BRACKET ATTACHMENT LOCATIONS

CANADA DEPARTMENT OF TRANSPORT AIRCRAFT CERTIFICATION BRANCH DAO # 01-O-01

APPROVED

C.PROVENCAL (DE # 03)

DATE: CERT. NO .: ISSUE NO .:


21.09.09 SH19-31 / SH18-9 1/1

DESIGN	N SAD	DART AEROSPA	ACE L'	TD
REV.	DESCRIPTION		BY	DATE
Α	NEW ISSUE			21.09.01
В	601.0733 USED FWD/AFT (SECTION 2), FIX P/N TYPOS (SHT 2), ADD 601.0625 & HARDWARE TO KIT (SECTION 3), UPDATE PARTS LIST			21.09.09

DRAWN SAD HAWKESBURY, ONTARIO, CANADA PPROVED DRAWING NO. CHECKED HE DSI 9865 MFG. APPR. N/A SHEET 1 OF 4 TITLE **APPROVED** CP 505 FLOAT ATTACHMENT DE APPR. CP U


COPYRIGHT © 2021 BY DART AEROSPACE LTD. 21.09.09

NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.




D3672-7 WASHER B WEARPLATE, REF D2652 BUSHING 601.4106 LOOP CLAMP NAS1149C0332R WASHER MS21043-3 NUT

SECTION A-A




D3672-7 WASHER B D2652 BUSHING 601.4106 LOOP CLAMP NAS1149C0332R WASHER MS21043-3 NUT

SECTION B-B



SECTION C-C



DETAIL D

DESIGN	SAD	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	SAD		
CHECKED	HE	DRAWING NO. REV.	В
MFG. APPR.	N/A	DSI 9865 SHEET 2 OI	F 4
APPROVED	CP	TITLE SCA	LE
DE APPR.	CP W	505 FLOAT ATTACHMENT N	TS
DATE 21.09.09		COPYRIGHT © 2021 BY DART AEROSPACE LTD. THIS DOCUMENT IS PRIVATE AND COMPIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPAGE LTD.	

APPROVED

3.0 CHANGE: L-BRACKET REPLACEMENT ON AFT SADDLE

The 601-0733 L-Bracket (F/N 51) shown in Figure 31 of II505-1 will not install on the aft saddle of DART D505-1057-XXX Skidtube Installations. Alternately, install an additional 601.0896 Loop Clamp (F/N 24) at the location shown in Figure 2 of this DSI. Install the 601.4106 Loop Clamp (F/N 25) and associated hardware similar to Section P-P of Figure 30 of II505-1.




FIGURE 2

4.0 TORQUE VALUE CORECTION, T-BOLT LOOP CLAMP

The torque value for the 651.2601 T-Bolt Loop Clamp, Section 4.3 of II505-1, is amended as follows:

WAS:

3. Torque T-Bolt Loop Clamp to 80-90 in-lbf.

IS:

3. Torque T-Bolt Loop Clamp to 45-50 in-lbf.

	DESIGN	SAD	DART AEROSPACE L	TD
	DRAWN	SAD	HAWKESBURY, ONTARIO, CANAL	
1	CHECKED	HE	DRAWING NO.	REV. B
	MFG. APPR.	N/A	DSI 9865	SHEET 3 OF 4
	APPROVED	CP	TITLE	SCALE
	DE APPR.	CP W	505 FLOAT ATTACHMENT	NTS
	DATE 21.09.09		COPYRIGHT © 2021 BY DART AEROSPACE LTD. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM ABET AEROSPACE LTD.	

5.0 PARTS LIST, FLOAT ATTACHMENT KIT

The DSI 9865-011 Float Attachment Kit provides additional hardware to allow installation of the DART 651.600X-series Emergency Float System on DART D505-1057-013/-014/-113/-114 Skidtube Installations. Qty(1) kit contains sufficient hardware to install qty(1) float system onto qty(2) skidtubes.



QTY -011	Part Number	Description	
Х	DSI 9865-011	FLOAT ATTACHMENT KIT, 505	
2	601.4106	LOOP CLAMP (MS21919WDG7)	
2	601.0896	LOOP CLAMP (MS21919WDG35)	
2	AN3C5A	BOLT (OR 601.0720)	
2	AN3C36A	BOLT	
6	AN3C37A	BOLT	· · · · · · · · · · · · · · · · · · ·
4	AN3C42A	BOLT	
4	D2652	BUSHING	
20	D3672-7	WASHER	
12	MS21043-3	NUT (OR 601.0789)	West 60
10	NAS1149C0332R	WASHER (OR 601.2421)	
4	NAS1149C0363R	WASHER (OR 601.0774)	

6.0 WEIGHT AND BALANCE

This DSI has negligible effect on weight and balance.

Ш
>
0
α
0
О,

DESIGN	SAD	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	SAD		
CHECKED	HE	DRAWING NO.	REV. B
MFG. APPR.	N/A	DSI 9865	SHEET 4 OF 4
APPROVED	CP	TITLE	SCALE
DE APPR.	CP UT	505 FLOAT ATTACHMENT	NTS
DATE 21.0	9.09	COPYRIGHT © 2021 BY DART AEROSPACE LTD. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT	